

THE TECHNOLOGY

The ActivePure® Guardian Air & Surface Pro combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure Technology. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure[®] Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia herbicola

- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The ActivePure Beyond Guardian Air provides surface decontamination and air purification. It is a proactive and effective solution for your home or business.

- · Portable, light weight device
- No installation plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi
- Reduces smoke, allergens, odors, and VOC gases
- Multiple carbon brushes aid in the capture of contaminants



¹View test results at ACTIVEPURE.COM/SCIENTIFIC-PROOF

Devices with ActivePure® Technology have been proven to reduce

99.99%

of many common types of bacteria, viruses, and mold spores, including the virus which causes COVID-19¹

ActivePure

GUARDIAN AIR & SURFACE PRO

Product Information	O0764 Model: F159K Meets California ozone emissions limit. CARB Certified Validated to UL 2998 VALIDATED • ZERO OZONE EMISSIONS - MEASURED OZONE EMISSIONS FROM APCO FAMILY DURING USE PHASE DOES NOT EXCEED 0.005
Technology Included	ActivePure® Technology - (1) 9" Cell HEPA Filter Activated Carbon Carbon Brushes
Electrical	Input Voltage: 120 VAC 60 Hz Power Consumption: 23 Watts to 80 Watts
Mechanical	Motor: 230 VAC 0.28 Amp Air Exchange: 4.2 changes per hour (351 / sq. ft.)
Safety	Complies to UL 867
Weight & Dimensions	34 lbs (15.5 kg) 23" H x 20" W x 11" D (58.4 cm x 50.8 cm x 27.9 cm)
Operating Temperature	(Return Air) 30° F to 95° F (-1°C – 35°C)
Sound Level	Speed 1: 32 dB(A) Speed 2: 39 dB(A) Speed 3: 46 dB(A) Speed 4: 58 dB(A)
Recommended Maximum Coverage in a	Up to 2,500 sq. ft. (232 m²) depending on occupant density and other factors. High density commercial not to exceed 1,000 sq. ft. (92 m²).

Warranty Limited 3 year warranty

 Assumes an 8-foot ceiling. Solutions should be customized based upon a variety of factors including HVAC system capabilities, HVAC settings, air flows (taking into account walls, air pressure, and doors), ambient air temperature, humidity, variable density, known VOC concentrations, and other layers of protection.

For coverage in medical or health care environments, contact Medical@activepure.com.





Contiguous Space¹

ActivePure Technology is available in HVAC, Induct units and portable, plug-and-play units.

