

This unaffiliated laboratory testing was done on the lowest setting using only ActivePure® Technology.

THE TECHNOLOGY

The ActivePure® Surface & Air Guardian combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure Technology. Patented ActivePure is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia herbicola

- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The ActivePure Surface & Air Guardian provides 24/7 surface decontamination and air purification without the use of ozone. It is a proactive and effective solution for your home or business.

- Portable, lightweight device
- No installation plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi
- Reduces smoke, allergens, odors, and VOC gases without the use of ozone
- Multiple carbon brushes aid in the capture of contaminants

Devices with ActivePure® Technology have been proven to reduce

99.99%

of many common types of bacteria, viruses, and mold spores, including the virus which causes COVID-19¹



¹View test results at ACTIVEPURE.COM/SCIENTIFIC-PROOF



SURFACE & AIR GUARDIAN

00763 Model: A1040F (ozone-free)

Product Information Meets California Ozone Emissions Limit. Carb Certified.

Validated to UL 2998

ActivePure® Technology – (2) 6" Cells

Technology Included HEPA Filter Screen

Activated Carbon Filter

Carbon Brushes

Input Voltage: 100 ~ 240 VAC; 50/60 Hz

Electrical External Power Supply; DC 24 Volts; 1.5 Amps Max.

Power Consumption: 43 Watts Max.

Mechanical Nominal Airflow Rate: 40-60 CFM Adjustable Fan Speed

Safety Conforms to UL 867

Weight & Dimensions 7.6 lbs (3.5 kg)

11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)

Operating Temperature 34°F – 100°F (-1°C – 38°C)

Sound Level 45 dB(A) (on low); 55 dB(A) (on high)

Recommended Maximum Coverage in a Contiguous

Space1

Up to 2,000 sq. ft. (185 m^2) depending on occupant density and other factors.

High density commercial not to exceed 500 sq. ft. (46 m²).

For coverage in medical or health care environments, contact Medical@activepure.com.

Warranty Lim

Limited 3 year warranty

Assumes an 8-foot ceiling. Solutions should be customized based upon a variety of factors including HVAC system
capabilities, HVAC settings, air flows (taking into account walls, air pressure, and doors), ambient air temperature, humidity,
variable density, known VOC concentrations, and other layers of protection.

Let us show you more!



ActivePure Technology is available in HVAC, Induct units and portable, plug-and-play units.

