

# Proactive Surface & Air Purification for the Modern Home

## Meet ActivePure® Technology



The Induct line of products feature ActivePure Technology proven to reduce viruses, bacteria, and other pathogens<sup>1</sup>

### THE TECHNOLOGY

The Induct line of products attach directly to the HVAC ductwork to reduce viruses, bacteria, and other contaminants in the air and on surfaces in homes up to 8,000 sq. ft. per unit (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

### THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens<sup>1</sup>:

- SARS-CoV-2
- *Listeria monocytogenes*
- *Staphylococcus aureus*
- Murine Norovirus
- *Aspergillus niger endospores*
- *E. coli*
- H1N1 Influenza
- *Candida auris*
- H5N8 Influenza
- *Botrytis cinerea*
- MRSA
- *Sclerotinia sclerotiorum*
- *Bacillus globigii*
- *Legionella pneumophila*
- MS2 Bacteriophage
- *Aspergillus versicolor*
- *Staphylococcus epidermidis*
- *Clostridium difficile*
- PhiX-174
- *Salmonella enterica*
- *Erwinia herbicola*

### THE BENEFITS

The Induct line of products provides a proactive and effective purification solution for your home.

- Provides surface and air purification without the use of ozone<sup>1</sup>
- Reduces allergens and other common contaminants
- Protects your heating and cooling system from potential buildup

Devices with ActivePure® Technology have been proven to reduce

# 99.99%

of many common types of bacteria, viruses, and mold spores, including the virus which causes COVID-19<sup>1</sup>



<sup>1</sup>View test results at [ACTIVEPURE.COM/SCIENTIFIC-PROOF](https://activepure.com/scientific-proof)



**INDUCT  
GUARDIAN**

**INDUCT  
GUARDIAN DUAL**

**INDUCT  
GUARDIAN I**

**INDUCT  
GUARDIAN II**

**INDUCT  
GUARDIAN III**

**INDUCT  
GUARDIAN IV**

**Product  
Information**

00774  
Model: A1023E  
(ozone free)

00780  
Model: B1025A  
(ozone free)

00761  
Model: B1013U  
(ozone free)

00766  
Model: A1024F  
(ozone free)

00767  
Model: A1025F  
(ozone free)

00768  
Model: A1033B  
(ozone free)

**Environmental  
Certifications**

**Models: A1023E; B1025A; B1013U; A1024F; A1025F and A1033B Meet California ozone emissions limit. CARB Certified**  
**Models: A1023E; B1025A; B1013U; A1024F; A1025F and A1033B are validated to UL 2998**



**Electrical**

Input Voltage:  
100~240 VAC;  
50/60 Hz  
Current: 0.17 Amps  
Power: 19 Watts

Input Voltage:  
100-277 VAC; 60 Hz  
Current: 0.75 Amps  
Power: 90 Watts

Input Voltage:  
24 VAC; 50/60Hz  
Current: 1.0 Amps  
Power: 17 Watts

Input Voltage:  
120/277 VAC;  
50/60 Hz  
Current: 0.27 Amps  
Power: 20 Watts

Input Voltage:  
120/277 VAC;  
50/60 Hz  
Current: 0.54 Amps  
Power: 37 Watts

Input Voltage:  
100V-277 V; 50/60 Hz  
Current: 1.05 Amp Max  
@ 120V 126W  
Power: 0.57 Amp Max  
@ 220V 125W

**Mechanical**

Distribution via air handler. Safety Switch Installed.

**Safety**

Conforms to UL 1995.

**Recommended  
Maximum  
Coverage  
in a Contiguous  
Space<sup>1</sup>**

Up to 1,000 sq. ft.  
(92 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 500 sq. ft.  
(46 m<sup>2</sup>).

Up to 2,500 sq. ft.  
(232 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 1,250 sq. ft.  
(116 m<sup>2</sup>).

Up to 1,000 sq. ft.  
(92 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 500 sq. ft.  
(46 m<sup>2</sup>).

Up to 2,500 sq. ft.  
(232 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 1,250 sq. ft.  
(116 m<sup>2</sup>).

Up to 5,000 sq. ft.  
(464 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 2,500 sq. ft.  
(232 m<sup>2</sup>).

Up to 8,000 sq. ft.  
(743 m<sup>2</sup>) depending  
on occupant density  
and other factors.<sup>1</sup>  
High density  
commercial not to  
exceed 4,000 sq. ft.  
(371 m<sup>2</sup>).

**Operating  
Temperature**

34°F – 200°F

**Dimensions**

8.5" H x 8.5" W x 11" D

8.5" H x 9.75" W x 11.5" D

8.5" H x 8.5" W x 11" D

9" H x 9" W x 17" D

8.5" H x 9.75" W x 17" D

11" H x 11" W x 17" D

**Weight**

3 lbs.

6 lbs.

3 lbs.

4 lbs.

8 lbs.

8 lbs.

**Warranty**

Limited 5 year warranty

1. Assumes an 8-foot ceiling. Solutions should be customized based upon a variety of factors including HVAC system capabilities, HVAC settings, air flows (taking into account walls, air pressure, and doors), ambient air temperature, humidity, variable density, known VOC concentrations, and other layers of protection.



*Let us show you more!*

ActivePure Technology is available in HVAC, Induct units and portable, plug-and-play units.



ACTIVEPURE.COM